

起重量 Lifting Weight		t	5/5								10/10								16/16																															
跨度 Span		m	10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5	10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5	19.5	22.5	25.5	28.5	31.5																											
最大起升高度 Max. Lifting Height		m	20/22								18/22								22																															
工作级别 Working Class		A6																																																
速度 Speed	起升 Lift	m/min	40.1/15.4								40.26/14.5								41.8/13																															
	小车运行 Handcar Travel		44.6								45.6								43.2																															
	小车运行 Cart Travel		93.7				113				112.5				101				98				87.3																											
电机 Motor	起升 Lift	抓斗 Grab Hook	YZR225-8/22								YZR208S-10/37								YZR315M-10/75																															
		吊钩 Hook	YZR180L-6/15								YZR225M-8/22								YZR250M1-6/37																															
	小车运行 Handcar Travel	YZR132M2-6/3.7								YZR160M1-6/5.5								YZR160M2-6/7.5																																
	小车运行 Cart Travel	YZR160M2-6/7.5×2	YZR160L-6/11×2				YZR160M2-6/7.5×2				YZR160L-6/11×2				YZR200L-8/15×2																																			
主要尺寸 (mm) Main Size	B	6355				6485				7090				6385				6485				7145				6870				7000																				
	Ba	4000				4100				5000				4000				4100				5000				4800				5000																				
	BX	3550								4420								5250																																
	b	230								230								250								250				300																				
	LX	2000±2								2000±2								2500																																
	H	1893				1943				2095				2185				2418				2548																												
	H1	254	260	270	285	300	310	325	340	255	261	276	277	292	307	322	332	292	294	309	319	329	8	8	8	8	8	8	8	0	0	0	0	0	0	0	0	4	4	4	4	4								
	H2	735				785				785				890				880				1010																												
	S1	1520								1700(1800)								2175(2275)																																
	S2	1500								1500(1600)								1575(1675)																																
	F	128	228	328	478	628	728	878	1028	130	230	380	380	530	680	830	930	544	564	714	814	914																												
	h	2020								2550								2795																																
重量 Weigh t	小车 Handcart	7.6(8.4)								11.5(12.5)								19.9(21)																																
	总重量 Total Weigh t	22.7	24.4	26.4	29.2	32	36.8	40.5	43.8	26.5	28.4	31.1	35	38.4	43	46.8	50.4	56.4	60.3	64.8	67.7	72	Indoor																											
		23.7	25.3	27.3	30.1	32.9	37.7	41.4	44.7	27.4	29.3	32.5	35.8	39.3	43.9	47.8	51.2	57.6	61.7	66.2	69.1	73.5	Outdoor																											
最大轮压 Max. Wheel Pressure	室内 Indoor	10.2	10.9	11.6	12.7	13.1	14.7	15.8	16.8	14.8	15.9	17.3	18.6	19.6	20.9	21.9	22.9	27.3	28.4	30.6	31.7	32.1																												
	室外 Outdoor	10.6	11.3	12	13.1	13.4	15.1	16.1	17.1	15.2	16.3	17.7	19	19.9	21.3	22.3	23.3	27.9	28.8	30.9	32	32.4																												
抓斗 Grab	型号 Model	u	113	109	110	105	106	101	102	127	123	124	119	120	115	116	141	137	138	133	134	129	130																											
	类型 Type	轻型 Light	中型 Medium				重型 Heauy				超重型 spuer heavy				轻型 Light				中型 Medium				重型 Heauy				超重型 spuer heavy																							
	容积 Volume	m3	2.5	1.5				1				0.75				5				3				2				1.5				8				4.8				3.2				2.5						
	容重 Density	t/m3	≤1	>1-1.7				>1.7-2.5				>2.5-3.3				≤1				>1-1.7				>1.7-2.5				>2.5-3.3																						
	自重 Dead Weight	kg	2633	2549	2615	2506	2568	2479	2546	4800	4803	4866	4850	4913	4730	4793	7841	7993	8143	8008	8159	8155	8305																											
	主要尺寸 (mm) Main Size	Ba	1634				1444				1238				1160				2060				1764				1528				1416				2350				2078				1792				1628			
		Bb	2425				2175				2025				1875				2970				2670				2470				2230				3515				3135				2915				2665			
Bc		3120	2740	2900	2530	2690	2340	2500	3900	3430	3590	3220	3380	3920	3080	4380	4050	4250	3750	3950	3430	3630																												
Hp		3135	293	301	283	291	273	281	3990	374	382	364	372	349	357	4775	460	470	445	445	428	4385																												

			5	5	5	5	5	5		7	7	0	0	0	0		5	5	5	5	5	
	Hb	-3615	-338	-360	-325	-347	-312	-334	-4560	-429	-451	-412	-434	-391	-413	5530	524	548	497	521	481	5051
			5	5	5	5	5	5		7	7	5	5	0	0		3	3	9	9	1	
荐用钢轨 Recommend Steel Track			43kg/m													QU70 □90×90						
电源 Power Supply			三相交流 3-Phase A.C. 50Hz 380V																			

www.sino-lifting.com